

## PARTS

## INFORMATION BULLETIN

Voice Activation System Accessory –  
Prewiring Only On Certain  
2005 MY S-TYPE ModelsMODEL 2005 MY-ON  
S-TYPE  
VIN N13089-ON**IMPORTANT - PLEASE CASCADE TO ALL RELEVANT PERSONNEL****Issue:**

For 2005 MY, the voice activation pre-wiring is **no longer present on every S-TYPE** model.

The voice activation pre-wiring is present **only** on the following:

- S-TYPE R
- S-TYPE VDP
- Vehicles equipped with the **navigation** option

In order to install voice activation, the vehicle must be an S-TYPE R, S-TYPE VDP or have the **navigation** option.

This system allows the driver to operate the climate control system, the audio system, optional navigation system and the optional phone system by giving voice commands via the roof-mounted microphone.

The system is able to interpret most English speakers without difficulty but if some voice commands are not recognized, voice training for up to two people can be carried out to help better understand the system operator. This is described in the Voice Activation Handbook.

**COMPONENTS REQUIRED TO INSTALL THE VOICE ACTIVATION SYSTEM**

<b>Description</b>	<b>Part No.</b>
Voice activation module	XR8 34964
Fitting kit	XR8 36179
Voice activation handbook	JJM 1808265/01
Microphone (if needed)	C2S 15896
May also require D2B link lead	(see attached table)

**2005 MY ON S-TYPE D2B OPTION CHART**

ALL POSSIBLE OPTION COMBINATIONS	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32
MULTI CD	N	X		X		X		X		X		X		X		X	X	X	X	X	X	X	X	X								
PHONE	O		X	X			X	X			X	X			X	X		X	X	X	X	X	X	X		X		X		X		X
VOICE	N				X	X	X	X				X	X	X	X				X	X			X	X			X	X				X
NAV	E									X	X	X	X	X	X	X					X	X	X	X					X	X	X	X
PREMIUM ICE																	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X

To select correct telematics link lead from matrix below please read the following;

- 1) Establish the final specification of the vehicle once upgraded ( including existing features ) and locate the corresponding column indicated by 'X's in the D2B OPTION CHART.
- 2) Follow the column down to the USE LINK LEADS chart. Read off the corresponding link lead part numbers from chart as denoted by 'X's.

NB - Please note that depending on the options required 1 or 2 link leads will be required. Link leads must only be used as specified, no other combination is acceptable.

- USE LINK LEADS -																																	
XR8 49171	4R8T-18K925-AA			X		X		X																									
XR8 49172	4R8T-18K925-BA									X		X		X		X																	
XR8 49173	4R8T-18K925-CA																				X	X	X	X									
XR8 49174	4R8T-18K925-DA																	X	X	X	X												
XR8 49175	4R8T-18K925-EA							X		X		X		X																			
XR8 49176	4R8T-18K925-FA																													X	X	X	X
XR8 49177	4R8T-18K925-GA																									X	X	X	X				
XR8 49465	4R8T-14B548-AA														X															X			X
XR8 49466	4R8T-14B548-BA						X	X			X		X		X					X				X		X	X			X	X		
XR8 49467	4R8T-14B548-CA			X	X	X					X		X					X	X			X	X										
XR8 49468	4R8T-14B548-DA									X							X					X											

EXAMPLE;

FACTORY FIT OPTION ONLY

DLR INSTALLED ACCESSORIES

Link lead required for vehicle with existing telephone, upgrading vehicle to include CD Autochanger.  
 Final vehicle specification = CD and TELEPHONE.  
 Therefore two telematics link leads will be required, part numbers (XR8 49171 & XR8 49467)