JAGUAR SERVICE

Issue Date 01/2003

VEHICLE MAINTENANCE CHECKLIST

All 2003 Models

VEHICLE INFORMATION

VEHICLE OWNER | R.O. # | DATE

VIN | MODEL CODE | ODOMETER

MAINTENANCE CHECKLIST

Maintenance Intervals every 10,000 mi. (16,000 km) or 12 months, whichever occurs first.

NOTE: Protect the interior and fenders of the vehicle before proceeding.

MAINTENANCE INTERVAL (CHECK ONE):

	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
miles x 1,000:	**10**	**20**	**30**	**40**	**50**	**60**	**70**	**80**	**90**	**100**
kilometers x 1,000:	**16**	**32**	**48**	**64**	**80**	**96**	**112**	**128**	**144**	**160**
ENGINE COMPARTMENT										
Check / top up brake fluid level *	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
Check / top up coolant level; assure specific gravity	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
Check / top up power assisted steering fluid level	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
Check / top up windshield washer fluid level	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
Check drive belt tension wear indicator(s); replace belt(s) if necessary or as specified	☐	☐	☐	☐	☐	☐	☐	☐	☐	
Check / top up battery electrolyte level (X-TYPE models only)	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
Check / adjust headlamp alignment (XJ models only)		☐		☐		☐		☐		☐
Visually check for fluid leaks	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
Replace air filter element				☐				☐		
Replace fuel filter (all models except X-TYPE)						☐				
Replace fuel filter (X-TYPE models only)							☐			
Replace pollen filter (XJ and X-TYPE models)		☐		☐		☐		☐		☐
Replace pollen filter (XK and S-TYPE models)	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
Replace engine coolant	– every 5 years or 150,000 miles (240,000 kilometers) –									
Replace spark plugs										☐
Replace accessory drive belt (XJ, XK and S-TYPE models)	– every 150,000 miles (240,000 kilometers) –									
Replace rear drive belt (X-TYPE models only)							☐			
Replace Supercharger drive belt										☐
TRUNK										
Check / top up battery electrolyte level (XJ, XK and S-TYPE models)	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
Check spare tire pressure, tread depth and general condition; record tread depth below **	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
UNDERBODY										
Replace engine oil, filter and drain plug washer	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
Inspect brake pads for wear; check rotor condition on pad change	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
Visually check for fluid leaks	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
EXTERIOR										
Replace windshield wiper blade rubber insert(s) (all models except X-TYPE)	☐	☐	☐		☐	☐	☐		☐	☐
Replace windshield wiper blade(s) and insert(s) (all models except X-TYPE)				☐				☐		
Check tire pressures, tread depth and general condition; record tread depth below **	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
Perform comprehensive road test; verify parking brake operation; record comments below	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐

OTHER PROCEDURES

* REPLACE BRAKE FLUID EVERY 2 YEARS: ☐ 2-YR. MAINTENANCE ☐ 4-YR. MAINTENANCE ☐ 6-YR. MAINTENANCE

** RECORD TIRE TREAD DEPTH: LH FRONT RH FRONT LH REAR RH REAR SPARE

COMMENTS

TECHNICIAN NAME | SIGNATURE