

DATE	VEHICLE REG. NO.	SPEEDO	INVOICE JOB NO.
------	------------------	--------	-----------------

**VIN RANGE**

2001.5 MY – From C00344 to C59260  
2002.25 MY – From C59261 Onwards

Maintenance must be carried out at 16 000 km (10 000 miles) or 12-monthly intervals from date of delivery, whichever comes first.

The Service Check Lists may be revised periodically. Franchise holders will be notified of revisions by Service Policy Letters or Technical Bulletins.

	16 000 km 10 000 miles	32 000 km 20 000 miles	48 000 km 30 000 miles	64 000 km 40 000 miles	80 000 km 50 000 miles	96 000 km 60 000 miles
Renew engine oil and oil filter. Renew drain plug sealing washer. Renew drain plug assembly.	X	X	X	X	X	X
Visually check underbonnet/underbody for any fluid leaks.	X	X	X	X	X	X
Inspect brake pads for wear (brake disc condition on pad change).	X	X	X	X	X	X
Renew coolant.	Every 5 years or 240 000 km (150 000 miles)					
Renew brake fluid.	Every 2 years					
Renew air cleaner element (Normally Aspirated).			X			X
Renew fuel filter.	112 000 km (70 000 miles)					
Renew spark plugs (Normally Aspirated).	112 000 km (70 000 miles)					
Renew spark plugs (leaded fuel markets only).	X		X		X	
Check accessory drive belt tension wear indicator(s) – replace belt(s) if necessary.	X	X	X	X	X	X
Renew front accessory drive belt.	160 000 km (100 000 miles)					
Renew rear accessory drive belt.	160 000 km (100 000 miles)					
Check/top-up brake fluid level.	X	X	X	X	X	X
Check/top-up coolant level.	X	X	X	X	X	X
Check/top-up windshield washer reservoir.	X	X	X	X	X	X
Check/top-up power steering fluid level.	X	X	X	X	X	X
Check/top-up battery electrolyte level.	X	X	X	X	X	X

	16 000 km 10 000 miles	32 000 km 20 000 miles	48 000 km 30 000 miles	64 000 km 40 000 miles	80 000 km 50 000 miles	96 000 km 60 000 miles
Visually inspect wiper blades for signs of wear or deterioration (see Note below).	X	X	X	X	X	X
Check tyre pressures, tread depth, general condition, signs of uneven wear and suitability (including spare tyre).	X	X	X	X	X	X

	Front	Rear	Spare
Right-hand	<input style="width: 50px; height: 20px;" type="text"/> mm	<input style="width: 50px; height: 20px;" type="text"/> mm	<input style="width: 50px; height: 20px;" type="text"/> mm
Left-hand	<input style="width: 50px; height: 20px;" type="text"/> mm	<input style="width: 50px; height: 20px;" type="text"/> mm	<input style="width: 50px; height: 20px;" type="text"/> mm

Renew pollen filters.		X		X		X
Carry out road test.	X	X	X	X	X	X

**Note:**

Wiper blades should only be replaced if authority is given by the vehicle owner.



**2.0 Litre, 2.5 Litre and 3.0 Litre V6 X-TYPE**  
**Vehicle Maintenance Sheet**

COMMENTS

SIGNATURE \_\_\_\_\_