

Dynojet Research Inc.
Run Name: C:\Users\B-Love\Downloads\RunFile_003 (2).drf
Run Title:
Run Notes:
Run Date: 1/31/2014 11:35:11 PM

RunFile_003 (2).drf: 76.04 °F 30.17 in-Hg Humidity: 20 % SAE: 0.97 Average Gear Ratio: 51.02

s	RPM x1000	hp	ft-lbs	Air/Fuel	
0.32	2.60	185.26	374.17	14.00	
0.47	2.70	194.46	378.27	13.54	
0.61	2.80	203.86	382.35	13.15	
0.76	2.90	214.81	389.05	12.95	
0.90	3.00	221.58	387.92	12.85	
1.06	3.10	231.18	391.68	12.79	
1.21	3.20	235.84	387.09	12.78	
1.33	3.30	244.01	388.35	12.80	
1.45	3.40	252.75	390.43	12.80	
1.57	3.50	262.01	393.16	12.80	
1.70	3.60	272.30	397.26	12.81	
1.81	3.70	280.25	397.81	12.83	
1.93	3.80	289.76	400.47	12.84	
2.04	3.90	298.42	401.89	12.86	
2.16	4.00	305.40	400.99	12.90	
2.28	4.10	313.69	401.83	13.00	
2.43	4.20	321.01	401.42	13.08	
2.61	4.30	327.12	399.56	13.09	
2.83	4.40	333.49	398.07	13.06	
3.01	4.50	341.75	398.87	13.02	
3.18	4.60	349.24	398.76	12.96	
3.33	4.70	356.40	398.26	12.90	
3.49	4.80	364.48	398.81	12.87	
3.64	4.90	371.99	398.72	12.83	
3.79	5.00	379.86	399.01	12.80	
3.94	5.10	387.93	399.50	12.76	
4.08	5.20	396.26	400.23	12.71	
4.23	5.30	404.98	401.32	12.61	
4.37	5.40	412.94	401.62	12.48	
4.52	5.50	422.08	403.06	12.34	
4.67	5.60	429.13	402.47	12.21	
4.83	5.70	437.00	402.67	12.08	
4.99	5.80	443.84	401.92	11.96	
5.17	5.90	448.71	399.44	11.85	
5.35	6.00	453.22	396.73	11.73	
5.53	6.10	455.67	392.33	11.55	
5.71	6.20	457.42	387.49	11.35	
5.90	6.30	457.89	381.74	11.15	
6.09	6.40	452.32	371.20	10.98	
6.27	6.50	451.69	364.97	10.67	
MAX:	6.27	6.50	457.89	403.06	14.00
MIN:	0.32	2.60	185.26	364.97	10.67

Dynojet Research Inc.
Run Name: C:\Users\B-Love\Downloads\RunFile_006.drf
Run Title:
Run Notes:
Run Date: 1/31/2014 11:35:28 PM

RunFile_006.drf: 69.32 °F 29.99 in-Hg Humidity: 53 % SAE: 0.98 Average Gear Ratio: 50.30

s	RPM x1000	hp	ft-lbs	Air/Fuel
0.40	2.50	187.15	393.12	14.73
0.56	2.60	198.17	400.28	14.78
0.71	2.70	209.90	408.29	14.74
0.85	2.80	218.55	409.94	14.78
0.99	2.90	228.88	414.50	14.83
1.14	3.00	237.23	415.34	14.86
1.28	3.10	243.06	411.79	14.87
1.43	3.20	253.39	415.87	14.84
1.58	3.30	259.94	413.72	14.83
1.72	3.40	268.23	414.33	14.83
1.87	3.50	276.35	414.70	14.83
2.02	3.60	283.41	413.47	14.82
2.17	3.70	291.51	413.81	14.81
2.31	3.80	297.99	411.86	14.81
2.47	3.90	303.60	408.87	14.82
2.63	4.00	309.69	406.64	14.83
2.78	4.10	316.49	405.42	14.84
2.93	4.20	323.24	404.22	14.86
3.08	4.30	332.15	405.69	14.86
3.23	4.40	339.91	405.74	14.83
3.38	4.50	349.26	407.63	14.80
3.54	4.60	354.31	404.55	14.72
3.69	4.70	358.45	400.56	14.56
3.84	4.80	366.39	400.90	14.21
3.99	4.90	376.01	403.02	13.84
4.14	5.00	385.51	404.95	13.47
4.29	5.10	394.22	405.97	13.19
4.44	5.20	402.83	406.87	12.98
4.60	5.30	408.25	404.56	12.79
4.76	5.40	413.80	402.48	12.61
4.92	5.50	420.34	401.39	12.41
5.08	5.60	426.18	399.71	12.23
5.25	5.70	428.97	395.27	12.06

5.41	5.80	430.67	389.99	11.94
5.58	5.90	436.41	388.48	11.83
5.74	6.00	441.04	386.06	11.72
5.91	6.10	443.56	381.91	11.57
6.09	6.20	444.59	376.63	11.36
6.27	6.30	443.80	369.99	11.11
6.45	6.40	440.38	361.40	10.89
6.63	6.50	438.88	354.64	10.69

MAX:	6.63	6.50	444.59	415.87	14.87
MIN:	0.40	2.50	187.15	354.64	10.69

Dynojet Research Inc.

Run Name: C:\Users\B-Love\Downloads\RunFile_023.drf

Run Title:

Run Notes:

Run Date: 1/31/2014 11:35:49 PM

RunFile_023.drf: 68.09 °F 29.88 in-Hg Humidity: 58 % SAE: 0.98 Average Gear Ratio: 50.05

s	RPM x1000	hp	ft-lbs	Air/Fuel
0.45	2.40	176.04	385.15	14.42
0.61	2.50	187.96	394.83	14.07
0.78	2.60	199.15	402.28	13.76
0.93	2.70	210.28	409.04	13.56
1.08	2.80	220.89	414.32	13.41
1.23	2.90	231.66	419.56	13.28
1.39	3.00	238.70	417.92	13.18
1.53	3.10	247.55	419.40	13.11
1.67	3.20	256.22	420.50	13.10
1.81	3.30	270.31	430.21	13.10
1.95	3.40	280.06	432.61	13.12
2.09	3.50	291.99	438.14	13.13
2.22	3.60	304.49	444.21	13.12
2.35	3.70	317.51	450.68	13.11
2.49	3.80	328.46	453.98	13.09
2.62	3.90	338.90	456.38	13.05
2.75	4.00	351.33	461.30	13.03
2.88	4.10	362.75	464.68	13.07
3.01	4.20	372.64	465.99	13.09
3.15	4.30	380.30	464.51	13.07
3.28	4.40	387.94	463.06	13.06
3.41	4.50	396.51	462.79	13.08
3.55	4.60	399.34	455.97	13.11
3.68	4.70	406.11	453.81	13.14
3.82	4.80	411.87	450.67	13.17
3.96	4.90	421.60	451.89	13.19
4.10	5.00	429.28	450.94	13.21
4.24	5.10	434.09	447.03	13.21
4.38	5.20	441.22	445.65	13.12
4.52	5.30	447.26	443.22	13.00
4.67	5.40	456.62	444.11	12.83
4.81	5.50	459.75	439.03	12.68
4.96	5.60	464.58	435.73	12.55
5.10	5.70	469.57	432.66	12.44
5.26	5.80	473.63	428.91	12.32
5.41	5.90	477.44	425.01	12.20
5.56	6.00	482.06	421.98	12.07
5.71	6.10	484.85	417.46	11.94
5.87	6.20	486.73	412.32	11.79
6.03	6.30	489.28	407.91	11.66
6.19	6.40	487.12	399.76	11.57
6.35	6.50	490.58	396.39	11.43
6.54	6.60	472.83	376.28	11.31

MAX:	6.54	6.60	490.58	465.99	14.42
MIN:	0.45	2.40	176.04	376.28	11.31