

Services should be performed within 2,500 miles of the specified mileage. For example, the 10,000 mile service should be performed between 7,500 and 12,500 miles.

Should the vehicle have a high proportion of short journeys or operate in severe conditions, Jaguar Cars recommends that the maintenance procedures scheduled at 10,000-mile intervals be performed at intervals not to exceed 6 months.

Service (miles x 1,000)	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150
Check / top up brake fluid level	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Check / top up coolant level	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Check / top up power assisted steering fluid level	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Check / top up windshield washer fluid level	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Check / top up battery electrolyte level	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Check drive belt tension wear indicator(s); replace belt(s) if necessary or as specified	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Check suspension dampers for fluid or air leaks: XJ models only	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Visually check under hood and under body for any fluid leaks	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Replace air filter element: all XJ and S-TYPE models				•				•				•			
Replace air filter element: Normally Aspirated XK models, all X-TYPE models			•			•			•			•			•
Replace air filter element: Supercharged XK models		•		•		•		•		•		•		•	
Replace fuel filter: all models except X-TYPE						•						•			
Replace fuel filter: X-TYPE models only								•						•	
Replace brake fluid															Every 2 years regardless of mileage
Replace engine coolant															Every 5 years or 150,000 miles

Service (miles x 1,000)	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150
Replace spark plugs										•					
Replace accessory drive belt															•
Replace rear drive belt: X-TYPE models only															•
Replace Supercharger drive belt: XJ and S-TYPE models										•					
Replace Supercharger drive belt: XK models				•				•				•			
Replace engine oil, oil filter and sump washer	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Inspect brake pads for wear (check rotor condition on pad change)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Replace pollen filter: XJ and X-TYPE models only		•		•		•		•		•		•		•	
Replace pollen filter: XK and S-TYPE models only	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Inspect windshield wiper blades for wear or deterioration	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Apply Jaguar Screen Clean paste to the windshield exterior		•		•		•		•		•		•		•	
Check tire pressure, tread depth and general condition; check for signs of uneven wear; check that tires are correct size and type (check should include spare tire)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Conduct road test; verify parking brake operation	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Replace airbag SRS															Required every 15 years