

MAINTENANCE CHECK SHEET 2005MY XJ

NO	
INTERVAL O MIL (Fbousands) 10 20 30 40 50 60 70 80 90 MM (Thousands) 16 32 48 64 80 96 11 128 144 O "Mominal" distance values for normal driving. See Passport to Service for additional information. .	
O KM (Thousands) 16 32 48 64 80 96 112 128 144 0 "Nominal" distance values for normal driving. See Passport to Service for additional information. Impact to Service for additional information. 1. VEHICLE INTERIOR Impact warning indicators and horn Impact warning indicators and horn Impact to Service for additional information. Impact to Service for additional information. Check operation of all lights, warning indicators and horn Impact to Service for additional information. Impact to Service for additional information. Impact to Service for additional information. Check operation of all lights, warning indicators and horn Impact to Service for additional information. Impact to Service for additional information. Impact to Service for additional information. Check operation of parking brake Impact to Service for additional information. Impact to Service for additional information. Impact to Service for additional information. 1. UBGAGE COMPARTMENT Impact to Service for additional information. Impact to Service for additional information. Impact to Service for additional information. Check and top-up brake, PAS and windshield washer fluid Impact to Service for additional information. Impact to Service for add	
O "Nominal" distance values for normal driving. See Passport to Service for additional information. 1. VEHICLE INTERIOR Check operation of parking brake Check operation of anking brake Check operation of anking brake Check operation of windshield wiper/washer systems 2. VEHICLE EXTERIOR Inspect windshield wiper/washer systems 3. LUGGAGE COMPARTMENT Check spare tire pressure, condition and tread depth Check spare tire pressure, condition and tread depth Check coolant level and freeze protection level Check coolant level and freeze protection level Replace brake fluid Replace brake fluid Replace brake fluid Replace spare tire pressure, condition and tread depth Check accessory drive belt and (if equipped) Supercharger drive belt and freeze protection level Inspect accessory drive belt and (if equipped) Replace palment fluid Check accessory drive belt and (if equipped) Replace palment fluid Replace palment fluid Check accessory drive belt and (if equipped) Replace spare fluid Replace palment fluid Check accessory drive belt and (if equipped) Replace palment fluid Replace palment fluid Check accessory drive belt and (if equipped) Replace spare fluid Replace spare fluid Replace palment fluid Subser fluid Replace spare fluid Replace spare fluids Replace spare fluids	
Check operation of parking brake Check operation of all lights, warning indicators and horn Check operation of windshield wiper/washer systems Check operation of windshield wiper/washer systems 2. VEHICLE EXTERIOR Inspect windshield wiper/blades and rubber inserts Apply Jaguar Screen Clean Paste to windshield exterior 3. LUGGAGE COMPARTMENT Check spare tire pressure, condition and tread depth Check spare tire pressure, condition and tread depth Check onlar top-up battery electrolyte level 4. ENGINE COMPARTMENT Check and top-up brake, PAS and windshield washer fluid Check and top-up brake, PAS and windshield washer fluid Check and top-up brake, PAS and windshield washer fluid Check and top-up brake, PAS and windshield washer fluid Check and top-up brake, PAS and windshield washer fluid Check and top-up brake, PAS and windshield washer fluid Check and top-up brake, PAS and windshield washer fluid Check and top-up brake, PAS and windshield washer fluid Replace brake fluid Replace spark fluigs *Every 5 years or 55,0000 miles* Replace accessory drive belt (if equipped) *Every 5 years or 55,0000 miles* *Every 100,000 miles* *Every 10	
Check operation of all lights, warning indicators and horn Check operation of windshield wiper/washer systems	
Check operation of windshield wiper/lades and rubber inserts 	
2. VEHICLE EXTERIOR Inspect windshield wiper blades and rubber inserts Apply Jaguar Screen Clean Paste to windshield exterior 3. LUGGAGE COMPARTMENT Check spare tire pressure, condition and tread depth Check and top-up battery electrolyte level 4. ENGINE COMPARTMENT Check and top-up battery electrolyte level 4. ENGINE COMPARTMENT Check and top-up battery electrolyte level 4. ENGINE COMPARTMENT Check coalt level and freeze protection level Inspect accessory drive belt and (if equipped) Supercharger belt Replace batke fluid	
Inspect windshield wiper blades and rubber inserts Apply Jaguar Screen Clean Paste to windshield exterior	
Apply Jaguar Screen Clean Paste to windshield exterior	
3. LUGGAGE COMPARTMENT Check spare tire pressure, condition and tread depth Check and top-up battery electrolyte level 4. ENGINE COMPARTMENT Check and top-up brake, PAS and windshield washer fluid Check and top-up brake, PAS and windshield washer fluid Check and top-up brake, PAS and windshield washer fluid Check and top-up brake, PAS and windshield washer fluid Check and top-up brake, PAS and windshield washer fluid Replace tracessory drive belt and (if equipped) Supercharger belt Replace brake fluid Replace air-cleaner element AJ82766 Replace air-cleaner element AJ82766 Replace air-cleaner element AJ82766 Replace accessory drive belt "Every 100,000 miles, whichever comes first" Replace accessory drive belt "Every 100,000 miles, whichever comes first" Replace accessory drive belt "Every 100,000 miles" Replace accessory drive belt "Every 100,000 miles" Replace accessory drive belt "Inspect for brake pa	
Check spare tire pressure, condition and tread depth Check and top-up battery electrolyte level 4. ENGINE COMPARTMENT Check and top-up brake, PAS and windshield washer fluid Check and top-up brake, PAS and windshield washer fluid Check coolant level and freeze protection level Inspect accessory drive belt and (if equipped) Supercharger belt Replace brake fluid Replace brake fluid Replace arcleaner element AJ82766 Replace and the belt (if equipped) Replace accessory drive belt *Every 100,000 miles* Replace accessory drive belt (if equipped) *Every 100,000 miles* Replace accessory drive belt *Every 100,000 miles* Replace drow and, caliper leaks and disc condition Inspect for under vehicle fluid leaks Inspect for under vehicle fluid leaks Inspect	
Check spare tire pressure, condition and tread depth Check and top-up battery electrolyte level 4. ENGINE COMPARTMENT Check and top-up brake, PAS and windshield washer fluid Check and top-up brake, PAS and windshield washer fluid Check coolant level and freeze protection level Inspect accessory drive belt and (if equipped) Supercharger belt Replace brake fluid Replace brake fluid Replace onlant Replace arcleaner element AJ82766 Replace and the belt (if equipped) Replace accessory drive belt (if equipped) Replace spark plugs *Every 100,000 miles* Replace accessory drive belt (if equipped) Replace accessory drive belt *Every 100,000 miles* Replace drop ad wear, caliper leaks and disc condition Inspect for brake pad wear, caliper leaks Inspect for under vehicle fluid leaks Inspect for under vehicle fluid leaks Inspect for under vehicle fluid leaks Inspect brake lines and hoses, fuel lines, PAS hoses and unio	
Check and top-up battery electrolyte level Image: Compartment in the image: Check and top-up brake, PAS and windshield washer fluid Image: Check and top-up brake, PAS and windshield washer fluid Image: Check and top-up brake, PAS and windshield washer fluid Image: Check and top-up brake, PAS and windshield washer fluid Image: Check and top-up brake, PAS and windshield washer fluid Image: Check and top-up brake, PAS and windshield washer fluid Image: Check and the image: Chec	
4. ENGINE COMPARTMENT Check and top-up brake, PAS and windshield washer fluid Check coolant level and freeze protection level Inspect accessory drive belt and (if equipped) Supercharger belt Replace pollen filter Replace brake fluid Replace collent Replace brake fluid Replace spark plugs Replace spark plugs Replace accessory drive belt (if equipped) Replace accessory drive belt S. UNDER VEHICLE Check tire pressures, condition and tread depth Inspect for under vehicle fluid leaks Inspect for under vehicle fluid leaks Inspect for under vehicle fluid leaks Inspect brake pad wear, caliper leaks and unions for correct routing and hoses, fuel lines, PAS hoses and unions for correct routing and damage Replace engine oil, oil filter and drain plug washer C2C241611+5W30X7 Replace fuel fliter Yes / Yes / Yes / Yes / Yes / Yes / No No	
Check and top-up brake, PAS and windshield washer fluid Check coolant level and freeze protection level Inspect accessory drive belt and (if equipped) Supercharger belt Replace pollen filter C2C6884 Replace brake fluid Every 2 years regardless of mileage* Replace collant Every 5 years or 150,000 miles, whichever comes first* Replace spark plugs Every 100,000 miles* Replace spark plugs Every 100,000 miles* Replace accessory drive belt (if equipped) Replace accessory drive belt Every 100,000 miles* Check tire pressures, condition and tread depth Inspect for brake pad wear, caliper leaks and disc condition Inspect for under vehicle fluid leaks <li< td=""></li<>	
Check coolant level and freeze protection level Image: Check coolant level and (if equipped) Supercharger belt Inspect accessory drive belt and (if equipped) Supercharger belt Image: Check coolant level Replace brake fluid Image: Check coolant Replace brake fluid Image: Check coolant Replace air-cleaner element AJ82766 Replace spark plugs Image: Check coolant Replace spark plugs Image: Check coolant Replace accessory drive belt (if equipped) Image: Check coolant Replace accessory drive belt Image: Check coolant S. UNDER VEHICLE Image: Check coolant Check tire pressures, condition and tread depth Image: Check coolant Inspect for under vehicle fluid or air leaks Image: Check coolant Inspect for under vehicle fluid leaks Image: Check coolant Inspect for under vehicle fluid leaks Image: Check coolant Inspect for under vehicle fluid leaks Image: Check coolant Replace engine oi	
Inspect accessory drive belt and (if equipped) Supercharger belt Replace pollen filter C2C6884 C2C688 C	
Replace pollen filter C2C6884 Image: C2C6884 Image: C2C6884 <th image<="" td=""></th>	
Replace brake fluid *Every 2 years regardless of mileage* Replace air-cleaner element AJ82766 Replace engine coolant *Every 5 years or 150,000 miles, whichever comes first* Replace spark plugs *Every 100,000 miles* Replace Supercharger drive belt (if equipped) *Every 100,000 miles* Replace accessory drive belt *Every 150,000 miles* S. UNDER VEHICLE Check tire pressures, condition and tread depth * Inspect for brake pad wear, caliper leaks and disc condition * Inspect for under vehicle fluid leaks * Inspect for under vehicle fluid leaks * Inspect brake lines and hoses, fuel lines, PAS hoses and unions for correct routing and damage * Replace engine oil, oil filter and drain plug washer C2C41611+5W30X7 Check line * * * * * * * * * * * * * * * * * * * * * * * * * * * *	
Replace air-cleaner element AJ82766 Replace engine coolant *Every 5 years or 150,000 miles, whichever comes first* Replace spark plugs *Every 100,000 miles, whichever comes first* Replace Supercharger drive belt (if equipped) *Every 100,000 miles* Replace accessory drive belt *Every 100,000 miles* S. UNDER VEHICLE Check tire pressures, condition and tread depth * Inspect for brake pad wear, caliper leaks and disc condition * Inspect for under vehicle fluid rair leaks * Inspect for under vehicle fluid leaks * Inspect brake lines and hoses, fuel lines, PAS hoses and unions for correct routing and damage * Replace engine oil, oil filter and drain plug washer C2C41611+5W30X7 G. REMEDIAL WORK/SERVICE CAMPAIGN NEEDED Yes / Yes / Yes / Yes / Yes / No Yes / Yes / Yes / Yes / Yes / No	
Replace engine coolant *Every 5 years or 150,000 miles, whichever comes first* Replace spark plugs *Every 100,000 miles* Replace Supercharger drive belt (if equipped) *Every 100,000 miles* Replace accessory drive belt *Every 150,000 miles* S. UNDER VEHICLE *Every 150,000 miles* Check tire pressures, condition and tread depth *Every 150,000 miles* Inspect for brake pad wear, caliper leaks and disc condition *Every 100,000 miles* Inspect for under vehicle fluid or air leaks *Every 100,000 miles* Inspect for under vehicle fluid leaks *Every 100,000 miles* Inspect for under vehicle fluid leaks *Every 100,000 miles* Replace engine oil, oil filter and drain plug washer C2C41611+5W30x7 Replace fuel filter *Every 60,000 miles* G. REMEDIAL WORK/SERVICE CAMPAIGN NEEDED Yes / Yes / Yes / Yes / Yes / Yes / No	
Replace spark plugs *Every 100,000 miles* Replace Supercharger drive belt (if equipped) *Every 100,000 miles* Replace accessory drive belt *Every 150,000 miles* S. UNDER VEHICLE *Every 150,000 miles* Check tire pressures, condition and tread depth Image: Condition and tread depth Inspect for brake pad wear, caliper leaks and disc condition Image: Condition and tread depth Inspect for brake pad wear, caliper leaks and disc condition Image: Condition and tread depth Inspect for under vehicle fluid or air leaks Image: Condition and tread depth Inspect for under vehicle fluid leaks Image: Condition and tread depth Inspect for under vehicle fluid leaks Image: Condition and tread depth Inspect brake lines and hoses, fuel lines, PAS hoses and unions for correct routing and damage Image: Condition and tread depth Replace engine oil, oil filter and drain plug washer C2C41611+5W30x7 Image: For the time of th	
Every 100,000 miles Replace accessory drive belt *Every 150,000 miles* S. UNDER VEHICLE *Every 150,000 miles* Check tire pressures, condition and tread depth Image: Condition and tread depth Image: Condition and tread depth Inspect for brake pad wear, caliper leaks and disc condition Image: Condition and tread depth Image: Condit and tread depth Image: Condition and	
Every 150,000 miles *Every 150,000 miles* 5. UNDER VEHICLE Check tire pressures, condition and tread depth Inspect for brake pad wear, caliper leaks and disc condition Image: Colspan="2">Image: Colspan="2" Image: Colsp	
5. UNDER VEHICLE Check tire pressures, condition and tread depth Inspect for brake pad wear, caliper leaks and disc condition Inspect for brake pad wear, caliper leaks and disc condition Inspect for under vehicle fluid or air leaks Inspect for under vehicle fluid leaks Inspect brake lines and hoses, fuel lines, PAS hoses and unions for correct routing and damage Replace engine oil, oil filter and drain plug washer C2C41611+5W30x7 Replace fuel filter Yes / No Yes / No	
Check tire pressures, condition and tread depth Image: Check tire pressures, condition and tread depth Inspect for brake pad wear, caliper leaks and disc condition Image: Check tire pressures, condition Inspect for brake pad wear, caliper leaks and disc condition Image: Check tire pressures, condition Inspect suspension dampers for fluid or air leaks Image: Check tire pressures, condition Inspect for under vehicle fluid leaks Image: Check tire pressures, condition Inspect for under vehicle fluid leaks Image: Check tire pressures, condition Inspect brake lines and hoses, fuel lines, PAS hoses and unions for correct routing and damage Image: Check tire pressure, condition Replace engine oil, oil filter and drain plug washer C2C41611+5W30x7 Image: Check tire pressure, condition Image: Check tire pressure, condition Replace fuel filter Image: Check tire pressure, condition Image: Check tire pressure, condition Image: Check tire pressure, condition Image: Check tire pressure, condition Image: Check tire pressure, condition Replace fuel filter Image: Check tire pressure, condition Image: Check tire pressure, condition Image: Check tire pressure, condition Image: Check tire pressure, condition Image: Check tire pressure, condition Image: Check tire pressure, conditio	
Inspect for brake pad wear, caliper leaks and disc condition Inspect for brake pad wear, caliper leaks and disc condition Inspect suspension dampers for fluid or air leaks Inspect for under vehicle fluid leaks Inspect for under vehicle fluid leaks Inspect for under vehicle fluid leaks Inspect brake lines and hoses, fuel lines, PAS hoses and unions for correct routing and damage Inspect for under vehicle fluid leaks Replace engine oil, oil filter and drain plug washer C2C41611+5W30x7 Replace fuel filter Image: Tevery 60,000 miles* G. REMEDIAL WORK/SERVICE CAMPAIGN NEEDED Yes / Yes / No Yes / Yes / Yes / No Yes / Yes / No	
Inspect suspension dampers for fluid or air leaks Inspect suspension dampers for fluid or air leaks Inspect for under vehicle fluid leaks Inspect for under vehicle fluid leaks Inspect brake lines and hoses, fuel lines, PAS hoses and unions for correct routing and damage Image: C2C41611+5W30x7 Replace engine oil, oil filter and drain plug washer C2C41611+5W30x7 Image: C2C41611+5W30x7 Image: C2C41611+5W30x7 Image: C2C41611+5W30x7	
Inspect for under vehicle fluid leaks Inspect for under vehicle fluid leaks Inspect for under vehicle fluid leaks Inspect brake lines and hoses, fuel lines, PAS hoses and unions for correct routing and damage Image: C2C41611+5W30x7 Image: C2C41611+5W30x7 Replace engine oil, oil filter and drain plug washer C2C41611+5W30x7 Image: C2C41611+5W30x7 Image: C2C41611+5W30x7 Replace fuel filter Image: C2C41611+5W30x7 Image: C2C41611+5W30x7 Image: C2C41611+5W30x7 Image: C2C41611+5W30x7 Replace fuel filter Image: C2C41611+5W30x7 Image: C2C41611+5W30x7 Image: C2C41611+5W30x7 Image: C2C41611+5W30x7 Replace fuel filter Image: C2C41611+5W30x7 Image: C2C41611+5W30x7 Image: C2C41611+5W30x7 Image: C2C41611+5W30x7 Replace fuel filter Image: C2C41611+5W30x7 Image: C2C41611+5W30x7 Image: C2C41611+5W30x7 Image: C2C41611+5W30x7 G. REMEDIAL WORK/SERVICE CAMPAIGN NEEDED Yes / Yes / Yes / Yes / Yes / Yes / No Yes / Yes / Yes / Yes / No Yes / No Yes / No No<	
Inspect brake lines and hoses, fuel lines, PAS hoses and unions for correct routing and damage Image: The second seco	
routing and damage Image Image </td	
routing and damage Image Image </td	
Replace fuel filter *Every 60,000 miles* 6. REMEDIAL WORK/SERVICE CAMPAIGN NEEDED Yes / No Yes / No Yes / Yes / Yes / Yes / No Yes / Yes / No Y	
Yes/ Yes/ <th< td=""></th<>	
No N	
NO	
If fault lamps illuminated use IDS to find the faults and report If fault lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report If a ult lamps illuminated use IDS to find the faults and report	
7. ROAD TEST	
Perform comprehensive road test and verify the following:	
Correct operation of transmission interlock	
Condition and operation of seatbelts	
Operation of steering column and seat adjustment mechanisms	
Starter motor operates normally and engine starts easily	
Steering self-centers from left and right-hand turns	
Vehicle does not pull or wander to one side	
Vehicle does not pull or wander to one side	
Vehicle does not pull or wander to one side Brakes operate smoothly without judder, noise or pull to one side	
• Vehicle does not pull or wander to one side </td	
• Vehicle does not pull or wander to one side </td	



MAINTENANCE CHECK SHEET 2005MY XJ

NOTE: Some items do not need to be carried out at every service. All required steps in a specific service are identified in the column headed by the mileage/month by a box -

Services should be performed within 2,500 miles of the specified mileage. For example, the 10,000 mile service should be performed between
 Should the vehicle have a high proportion of short journeys or operate in severe conditions, Jaguar Cars recommends that the maintenance procedures scheduled at 10,000 miles be performed at intervals not to exceed six (6) months.

TIRE TREAD DEPTH (INC SPARE)	L/F:	R/F:
	L/R:	R/R:
	SPARE:	

TECHNICIAN COMMENTS AND REMEDIAL ACTION REQUIRED:

TECHNICIAN NAME: