

Mobil 1 Synthetic ATF

Most Advanced Synthetic Automatic Transmission Fluid

Product Description

Mobil 1 Synthetic ATF is a multi-vehicle, fully synthetic fluid designed to meet the demanding requirements of modern passenger vehicles.

Features and Benefits

Mobil 1 Synthetic ATF with SuperSyn Technology outperforms conventional ATFs and provides outstanding resistance to oil breakdown and deposits. The inherently high viscosity index and stability of Mobil 1 Synthetic ATF protects against thermal breakdown at high operating temperatures, while still providing outstanding performance at ambient temperatures as low as -54° C. Further, it improves overall transmission durability and cleanliness. Key features and benefits include:

Features	Advantages and Potential Benefits
Enhanced, long-term frictional properties	Improves and extends transmission efficiency, smooth shifting performance and fuel economy
Exceptional thermal and oxidation stability	Keeps transmissions clean to extend life and performance even under severe driving conditions
Outstanding film-strength and anti-wear properties	Significant wear reduction and longer transmission life
Excellent low-temperature fluidity	Provides prompt and reliable lubrication at ambient temperatures down to -54° C
Exceptional shear stability	Viscosity retention even under the severest heavy duty, high temperature operating conditions
Compatible with mineral ATF fluids and all common seal materials	Reduced concern in top-off emergencies and excellent leakage control

Applications

- Mobil 1 Synthetic ATF is a multi-vehicle formula recommended for use in modern high performance automobiles, SUV's, SUT's, vans and other light trucks requiring Dexron III , Ford Mercon and Mercon V performance levels
- Also recommended by ExxonMobil for Chrysler automatic transmissions
- Surpasses the off-highway power transmission requirements of Allison C-4
- Suitable for Caterpillar TO-2 applications
- Recommended for use in any power steering unit where a Dexron or Mercon fluid is recommended

Specifications and Approvals

Mobil 1 Synthetic ATF has the following builder approvals:

Allison C-4
Ford Mercon



Mobil 1 Synthetic ATF has the following builder approvals:

General Motors Dexron III

Mobil 1 Synthetic ATF is recommended for use in applications requiring:

Caterpillar TO-2

Vickers 35VQ25 Vane Pump Test

Sundstrand Piston Pump Test

Typical Properties

Mobil 1 Synthetic ATF

Viscosity, ASTM D 445

cSt @ 40° C	34
-------------	----

cSt @ 100° C	7.6
--------------	-----

Brookfield Viscosity, ASTM D 5293

-cP @ -40° C	5190
--------------	------

Viscosity Index, ASTM D 2270	199
------------------------------	-----

Pour Point, °C, ASTM D 97	-54
---------------------------	-----

Flash Point, °C, ASTM D 92	236
----------------------------	-----

Density @15° C kg/l, ASTM D 4052	0.86
----------------------------------	------

Color	Red
-------	-----

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Mobil 1 ATF are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit www.exxonmobil.com.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2001 Exxon Mobil Corporation. All rights reserved.