



Vehicle Maintenance Sheet

DATE	VEHICLE REG. NO.	SPEEDO	INVOICE JOB	NO.	
			,		
	<u>VIN RANGE</u>				
Maintenance must be carried out at	99 MY - From 853936 to 878717				
The Service Check Lists may be revised periodically. Franchise holders will be notified of revisions by Service Policy Letters or Technical Bulletins. 2000 MY – From F00103 to F2064					

Carry out road test.

	16 000	32 000	48 000	64 000	80 000	96 000
	km	km	km	km	km	km
	10 000	20 000	30 000	40 000	50 000	60 000
	miles	miles	miles	miles	miles	miles
Renew engine oil, oil filter and drain plug sealing washer.	X	X	X	X	Х	Х
Visually check underbonnet/underbody for any fluid leaks.	X	X	Х	Х	Х	Х
Inspect brake pads for wear (brake disc condition on pad change).	Х	Х	Х	Х	Х	Х
Renew coolant.						
– Up to VIN 878273	Every 4 years or 96 000 km (60 000 miles)					
– From VIN 878274	Every 5 years or 240 000 km (150 000 miles)					
Renew brake fluid.	Every 2 years					
Renew air cleaner element			v			
(Normally Aspirated).			X			X
Renew air cleaner element		Χ		Χ		X
(Supercharged only).						
Renew fuel filter.						Х
Renew spark plugs (Normally Aspirated).	112 000 km (70 000 miles)					
Renew spark plugs (Supercharged only).	48 000 km (30 000 miles)					
Renew spark plugs (leaded fuel markets only).	X		X		X	
Check accessory drive belt tension wear indicator – replace belt if necessary.	X	X	X	X	Х	Х
Renew accessory drive belt.	160 000 km (100 000 miles)					
Renew supercharger drive belt (Supercharged only).				X		

	16 000 km 10 000 miles	32 000 km 20 000 miles	48 000 km 30 000 miles	64 000 km 40 000 miles	80 000 km 50 000 miles	96 000 km 60 000 miles
Grease axle shaft universal joints.	Х	X	X	X	Х	Х
Check brake fluid level.	Х	X	X	X	X	X
Check coolant level.	Х	X	X	X	X	Х
Check specific gravity – up to VIN 878273	X	X	Х	X	X	Х
Check/top-up windshield washer reservoir.	X	Х	Х	Х	X	Х
Check battery electrolyte level.	Х	X	X	X	X	Х
Check power assisted steering fluid level.	X	X	X	X	X	Х
Renew windshield wiper blade rubber.	Х	X	X		X	X
Renew windshield wiper blade.				X		
Check tyre pressures, tread depth, general condition, signs of uneven wear and suitability (including spare tyre).	Х	Х	Х	Х	Х	Х
Front		Rear			Spare	

	rione		itteui		Spare		
Right-hand	m	nm		mm			
Left-hand	m	nm [mm		mm	
Renew pollen filters (where fitted).			Every 3 years or 112 000 km (70 000 miles) or more often in polluted conditions.				

Χ

Χ

Χ

Χ





Vehicle Maintenance Sheet

COMMENTS						
SIGNATURE						